

EAT•N

Powerware

Powerware® 9140 Uninterruptible Power System

Product Focus

Superior de-centralized power protection for medium- and high-density rack environments



Product Snapshot

Power Rating:	10 kVA/8 kW and 7.5 kVA/6 kW Single-phase in/single-phase out Three-phase in/single-phase out (manually selectable in HW version)
Nominal Input Voltage:	1/1: 230 Vac (200–240 Vac) 3/1: 220-240/380-415 Vac
Nominal Output Voltage:	220/230/240 Vac single phase
Frequency:	50/60 Hz (auto-sensing)
Configuration:	Online, double-conversion 6U rackmount, including batteries
Dimensions (WxDxH):	430 mm x 760 mm x 263 mm

Features

- Protects mission-critical rackmount applications from downtime, data loss /corruption, and process interruption by providing continuous, clean power with double-conversion, online topology
- Conserves valuable rack space with up to 10 kVA of power in only 6U of height, including batteries
- Pre-installed rackmount hardware significantly reduces installation time
- Modular, lightweight design facilitates installation and improves service time
- Upgradable from 7.5 kVA to 10 kVA, to accommodate system growth
- Blade-server compatible with standard IEC receptacles
- ABM® technology significantly increases battery life, resulting in more uptime and fewer battery replacements

Today's racks of IT equipment are requiring even greater power, from computer rooms and wiring closets to commercial data centers. Whether you manage the IT needs of a small-to-medium business or an entire commercial facility, you know it is a challenge to provide in-rack power protection for expanding loads in shrinking spaces.

Fortunately, technology advancements have also raised the power density of power protection systems. The Powerware® 9140 uninterruptible power system (UPS) delivers efficient, reliable power protection in only 6U of rack space, including batteries.

This double-conversion, online UPS resolves all nine common utility power problems and supplies clean, continuous power to all connected equipment. If utility power goes out altogether, there is no delay transferring to backup power, either to UPS batteries or an auxiliary generator.

Introducing the Powerware 9140 UPS



The Powerware 9140 UPS and one EBM occupy only 9U of rack space.

Easily install and service your UPS.

With the Powerware 9140 UPS, Eaton introduces a new standard in system availability. The key is an internal automatic bypass feature that allows the Powerware 9140 to continuously provide power to critical equipment while the system is serviced – even when the electronics are removed. A manual bypass switch in the chassis eliminates transfer time and allows for module repair and replacement without shutting down the load. And, with Eaton’s comprehensive range of monitoring, remote diagnostic, and field technician dispatch services, we can help expedite mean time to repair (MTTR) should the need arise.

You want to install and service your UPS quickly and efficiently. That’s why the Powerware 9140 comes with pre-installed rackmount hardware, and features modules that are user-replaceable. One person, working alone, can replace a battery module without disrupting data center operations or power to protected equipment. Or, should you need to replace your power module, that too can be removed by a single person. The UPS will automatically transfer to and from bypass when a module is removed and installed to provide uninterrupted power to the load.

POWERWARE 9140 RUNTIMES (in minutes)

VA	Watts	UPS				
		Internal Batteries	+1 EBM	+2 EBMs	+3 EBMs	+4 EBMs
1250	1000	80	137	189	275	365
2500	2000	31	61	99	138	181
3750	3000	18	38	68	92	121
5000	4000	12	27	52	69	90
6250	5000	9	21	42	55	72
7500	6000	7	17	35	46	60
8750	7000	6	14	31	40	51
10,000	8000	5	12	27	35	45

In today’s dynamic IT environment, data room footprints change quickly. If you find yourself frequently moving racks and other IT equipment, the Powerware 9140 can be configured with input and output cords. This version of our UPS is equipped with standard plugs and sockets, which means you don’t need an electrician to install your UPS with each move—offering you greater flexibility.

Optimise battery performance.

Standard internal batteries provide ride-through power until auxiliary power takes over or systems are gracefully shut down. At 10 kVA, you can extend runtime up to 45 minutes at full load with Extended Battery Modules (EBMs). Lower loads will see even greater runtimes. These 3U rackmount units use the same battery modules as those found inside the UPS, minimizing inventory requirements.

ABM technology significantly extends battery service life with a unique three-stage charging technique. The UPS automatically tests battery health and provides advance notification when preventive maintenance is needed.

Streamline operations with complete rackmount solutions from Eaton.

All Powerware 9140 UPS models and corresponding EBMs come with pre-installed rackmount hardware for easy installation in standard equipment racks. Also, all Powerware 9140 UPSs and EBMs come with seismic-mounting kits. Should your application specify Zone 4 seismic requirements, all hardware is included with the UPS and EBM.

For ease of operation and lowest total cost of ownership, you can count on Eaton for all your rackmount power protection and distribution needs, in addition to UPS and optional Extended Battery Modules.

Our line of rackmount Powerware Power Distribution Units (PDUs) distributes conditioned UPS power throughout one or more racks—simply, elegantly, and inexpensively. The basic PDUs offer standard input and output power connections. Eaton boasts multiple PDU models that can be connected to the output of the Powerware 9140, and distribute 240V power throughout your rack.

Additionally, small step-down transformer options deliver 120V output to power communications, monitoring, and other peripheral equipment. Three of our 3 kVA model options occupy only 2U of rack space; a 250 VA model offers space-saving 1U and 0U mounting options.



Modular, lightweight design allows for easy installation and service

Stay continually informed of UPS status.

For local monitoring, UPSs in this class offer only status indicators. The Powerware 9140 features both LEDs and an intuitive, multilingual LCD screen on the front of the unit. Which relays more in-depth operational information, communicates specific alarms and predictive service needs, and can be used to program certain features.

The Powerware 9140 UPS constantly monitors its own operation and sends alarms or takes action if it detects a potential problem. If it senses an issue—planned or unplanned—the UPS instantly transfers to battery or bypass source, and back to normal when the alarm condition passes, with no interruption in power.

Unify and centralise UPS management.

Every Powerware 9140 UPS comes with LanSafe® power management software that enables you to remotely monitor UPS and battery performance, establish prioritised shutdown of devices and applications, test all networked UPSs, analyse trends and network conditions, and stay informed with a pager and e-mail.

Connectivity is easy. The standard unit Powerware 9140 UPS comes with a USB port, and a serial port, and an X-Slot™ bay for additional communication options. With X-Slot interface cards, the UPS can communicate in a variety of networking environments, including the Web, as well as building management systems, environmental monitors, relay contact devices, multiple servers, and other UPSs.

Gain a new level of confidence.

Backed by a comprehensive warranty program, the Powerware 9140 UPS delivers reliable, efficient, and full-featured protection available for your organisation's critical electronics.

Eaton is a global leader in power quality and management solutions and was named by Frost & Sullivan as "Power Quality Company of the Year" 2004 and 2005 (May 2005). We have a long heritage of double conversion online UPSs with an install base of the Powerware 9140 UPS represents more than 40 years of expertise in power quality solutions.

Rackmount UPSs from Eaton deliver confidence—confidence that your rack environments are served by complete power condition-

Connectivity options offer maximum flexibility.

The standard unit is equipped with USB and RS-232 serial ports to communicate with power management software. You can customise your UPS by adding an interface card for other applications:



ConnectUPS Web/SNMP Card

Monitor the UPS from anywhere. Connect the UPS to the Ethernet network and Internet for secure monitoring and management using a standard Web browser or SNMP.



Modbus Card

Interwork with you existing Building Management System. A Modbus® Card enables real-time monitoring of UPS systems through a Building Management System or Industrial Automation System.



Relay Interface Card

Gather information from relay contact devices. Provide a dry-contact interface between the UPS and any relay-connected device, including the IBM® eServer® iSeries and a variety of industrial applications.



Multi-server Card

Independently manage diverse servers. A Multi-server Card enables up to six serially connected devices of mixed operating systems to be independently managed and controlled by a single UPS.



Environmental Monitoring Probe

Monitor environmental conditions. An optional Environmental Monitoring Probe remotely monitors temperature, humidity, and two user-supplied contacts/sensors, such as smoke and intrusion detection.

ing and battery backup, and confidence that Eaton will be with you for the long term with premium warranty coverage and expert technical support.

To find out more about how the Powerware 9140 UPS can protect your medium- and high-density rack applications, visit our Web site www.powerware.com.au, or contact us at 1300 UPS UPS (1300 877 877).

Powerware 9140 Technical Specifications

Power		General	
Ratings	10 kVA/ 8 kW for 220-240V nominal voltage 7.5 kVA/6 kW	Dimensions	HxWxD, mm
Topology	True double-conversion, online UPS	PW9140 UPS	263 x 430 x 760 (6U)
Electrical Input		PW9140 EBM	131 x 430 x 660 (3U)
Nominal Input Voltage		Weight	
Single-phase	220 – 240V	PW9140 UPS	115 kg
Three-phase	380/220V, 400/230V, 415/240V user selectable	PW9140 EBM	79 kg
Input Voltage Range		Battery Module	17 kg
Single-phase	174 – 288V (for 220 – 240V nominal output)	Power Module	18 kg
Three-phase	301–499V	UPS Bypass	Automatic on overload, overtemp, UPS failure, or removal of power module
Operating Frequency	45–55 Hz range for 50 Hz nominal; 55–65 Hz range for 60 Hz nominal	Overload to bypass	+/- 10% of 112 to 130% for 60 seconds, transfer
Input Power Factor	PF > 0.99	Environmental	
Input Current Distortion	<5% THD	RoHS Compliance	EU RoHS / WEEE Compliant
Electrical Output		Operating Temperature	0°C to 40°C
Single-phase	220V / 230V / 240V user-selectable	Transit and Storage Temperature	-20°C to +50°C
Output Voltage Regulation	+/- 2% static, +/- 10% dynamic	Relative Humidity	0 – 95% non-condensing
Efficiency	>90%	Audible Noise	<55 dBA at 1 metre
Output Frequency	Automatic selection of 50 Hz nominal (+/- 3.5 Hz) and 60 Hz nominal (+/- 3.5Hz)	Altitude	Operating 3000m, Transit 15000m
Battery Type	12V, 5 Ah, sealed, lead-acid, maintenance-free	Certifications	
Battery Runtime	See battery runtime chart	Safety Certifications	UL, cULus, NOM, TUV, CE
Battery Replacement	Modular, hot-swappable, user-replaceable	EMC Compliance	FCC, CE, VCCI, C-tick
Charger	2.5A charger to support up to 4 additional EBMs	Markings	
Start-On-Battery	Allows startup of UPS without utility input	Communications	
LCD Display	Multilingual Graphical LCD with backlight	LEDs	(4) LEDs for notice and alarm
Communication Ports	(1) USB, (1) RS-232 serial, (1) REPO	Communication Slot	(1) X-Slot communication bay
Power Management Software	Bundled software suite CD Powerware 9140 is HID-compliant		



Natural Power Solutions (VIC)
Unit 1, 40 Jellico Drive
Scoresby VIC 3179
T: 03 9764 8550
F: 03 9764 8770

Natural Power Solutions (QLD)
Unit 8, 210 Queensport Road
Murarrie QLD 4172
T: 07 3907 0222
F: 07 3907 0333

Natural Power Solutions (NSW)
Unit 8, 2-6 Waltham Street
Artarmon NSW 2064
T: 02 9906 6696
F: 02 9906 6434

Natural Power Solutions (WA)
Unit 20, 9 Inspiration Drive
Wangara WA 6065
T: 08 9302 6366
F: 08 6210 5915

Natural Power Solutions (ACT)
Unit 5, 82-84 Townsville Street
Fyshwick ACT 2609
T: 02 6239 3802
F: 02 6239 3811

www.nps.com.au