

# XTREME POWER CONVERSION S70

Line Interactive UPS // 120VAC

For more information, visit [www.xpcc.com/s70](http://www.xpcc.com/s70)



## Equip your office with reliable battery backup and protection from power outages

Power quality disturbances including voltage fluctuations, over voltage, under voltage, and voltage blackouts occur unexpectedly. In the event of any of these common power problems, the S70 UPS activates to protect all connected critical loads—ranging from your computer to your business telephone system.

The S70 streamlines installation to just a few simple steps, allowing backup power protection right out of the box. The smart LCD screen offers real-time monitoring of UPS parameters while shutdown and monitoring software enables UPS and remote device control over your network.

### PRODUCT SNAPSHOT

- › Available models: 500VA, 700VA, 1000VA, 1500VA, 2000VA
- › Smart LCD display
- › Automatic voltage regulation (AVR)
- › RoHS compliant
- › Primary applications: home or small office, desktop computers, routers, and switches
- › 3 years electronics, 3 years battery warranty (USA)

### FEATURES

**Ease of use**—plug-and-play functionality means the UPS is ready to start backing up your equipment right out of the box

**Sleek design**—modern and compact, perfect for use in any home office or small office setting

**Smart LCD display**—monitor UPS vitals and manage all power devices in your network via USB

**Longer battery life**—wide operating voltage range means less use of batteries, making them last longer

**USB communications & software CD**—enables plug and play communications between servers, desktops, and the UPS; offers seamless installation with Windows, Mac, Solaris, and Linux operating systems

**Battery runtime**—capable of up to 146 minutes of battery backup; for the S70 battery runtime chart, visit [www.xpcc.com/s70](http://www.xpcc.com/s70)

**\$25,000 load protection policy**—protection against damaged connected equipment

# MODEL SELECTION GUIDE

For more information, visit [www.xpcc.com/s70](http://www.xpcc.com/s70)

MODEL NUMBER		S70-500	S70-700	S70-1000	S70-1500	S70-2000	
INPUT	Capacity	500VA (300W)	700VA (420W)	1000VA (600W)	1500VA (900W)	2000VA (1200W)	
	Voltage	120VAC					
	Frequency	60Hz					
OUTPUT	Voltage	120VAC					
	Waveform	Sine wave (normal), simulated sine wave (battery mode)					
	Frequency	60Hz ± 1Hz					
	Transfer time	4ms (typical)					
BATTERY	Type	Sealed, maintenance-free lead acid					
	Battery quantity and size	(1) 12V 7AH	(1) 12V 9AH	(2) 12V 7AH	(2) 12V 9AH		
	Recharge	4–6 hours to 90% capacity					
PHYSICAL	UPS dimensions (W x D x H)	3.9 x 11.3 x 5.6 in		5.7 x 13.8 x 6.3 in	5.7 x 15.6 x 8.1 in		
	Shipping dimensions	5.5 x 13.1 x 8.7 in		7.5 x 17.4 x 10 in	9.1 x 19.3 x 11.3 in		
	UPS weight	9.5 lbs	10.8 lbs	17.6 lbs	24.5lbs	25.4 lbs	
	Shipping weight	10.1 lbs	11.5 lbs	19.4 lbs	27.1 lbs	28.0 lbs	
	Line cord	5 ft, 5–15P					4ft, 5–20P
	Receptacles	(4) 5–15R		(6) 5–15R	(8) 5–15R		
INDICATORS & ALARMS	LCD display	AC mode, battery mode, load/battery level, input/output voltage, overload fault, low battery					
	Data line protection	N/A		RJ45			
WARRANTY	3 years electronics and battery (2 years outside of USA)						
COMMUNICATIONS INTERFACE	USB						
INCLUDED IN BOX	Shutdown and monitoring software, USB cable, user manual						



**X-TREME**  
Power Conversion®

Protect your business.

XPC USA / Denver, CO / sales@xpcc.com

XPC EMEA / Rotterdam, NL / emea@xpcc.com

www.xpcc.com

©2013 Xtreme Power Conversion Corporation. All Rights Reserved. S70.01U (Rev 6/05/13)